

## **AMENDMENT TO THE SPECIFICATION**

In the Claims, please amend as follows:

1. (Original) A method for posting buffers for a non-posting TCP application, the method comprising:

posting at least one generic buffer located in a memory external to a host adapter; and

transferring incoming data for a TCP connection to said at least one posted generic buffer prior to the non-posting TCP application posting a TCP application posted buffer for said incoming data.

2. (Original) The method according to claim 1, further comprising allocating at least one generic buffer from a pool of available generic buffers upon receipt of said incoming data for said TCP connection.

3. (Original) The method according to claim 2, further comprising storing at least a portion of said incoming data in said allocated at least one generic buffer if said TCP application posted buffer is unable to accommodate said incoming data.

4. (Original) The method according to claim 1, further comprising determining whether said incoming data for said TCP connection transferred to said at least one posted generic buffer is in sequence.

5. (Original) The method according to claim 4, wherein said determining further comprises assembling said incoming data in said at least one posted generic buffer if said incoming data is out of sequence.

6. (Original) The method according to claim 5, further comprising ordering said at least one posted generic buffer using a TCP data placement sequence number for said out of sequence incoming data.

7. (Original) The method according to claim 1, further comprising polling said at least one posted generic buffer by the non-posting TCP application to determine when said at least one posted generic buffer contains data for said TCP connection.

8. (Original) The method according to claim 7, further comprising, in response to said polling, notifying the non-posting TCP application when said incoming data is stored in said at least one posted generic buffer.

9. (Original) The method according to claim 1, further comprising posting at least one generic buffer prior to said transferring of said incoming data for a TCP connection to at least a portion of available TCP application buffers.

10. (Original) The method according to claim 1, further comprising posting at least one posted generic buffer located in a memory internal to said host adapter.

11. (Original) A machine-readable storage, having stored thereon a computer program having at least one code section for posting buffers for a non-posting TCP application, the at least one code section executable by a machine for causing the machine to perform the steps comprising:

posting at least one generic buffer located in a memory external to a host adapter; and

transferring incoming data for a TCP connection to said at least one posted generic buffer prior to the non-posting TCP application posting a TCP application posted buffer for said incoming data.

12. (Original) The machine-readable storage according to claim 11, further comprising code for allocating at least one generic buffer from a pool of available generic buffers upon receipt of said incoming data for said TCP connection.

13. (Original) The machine-readable storage according to claim 12, further comprising code for storing at least a portion of said incoming data in said allocated at least one generic buffer if said TCP application posted buffer is unable to accommodate said incoming data.

14. (Original) The machine-readable storage according to claim 11, further comprising code for determining whether said incoming data for said TCP connection transferred to said at least one posted generic buffer is in sequence.

15. (Original) The machine-readable storage according to claim 14, further comprising code for assembling said incoming data in said at least one posted generic buffer if said incoming data is out of sequence.

16. (Original) The machine-readable storage according to claim 15, further comprising code for ordering said at least one posted generic buffer using a TCP data placement sequence number for said out of sequence incoming data.

17. (Original) The machine-readable storage according to claim 11, further comprising code for polling said at least one posted generic buffer by the non-posting TCP application to determine when said at least one posted generic buffer contains data for said TCP connection.

18. (Original) The machine-readable storage according to claim 17, further comprising code for notifying the non-posting TCP application when said incoming data is stored in said at least one posted generic buffer in response to said polling.

19. (Original) The machine-readable storage according to claim 11, further comprising code for posting at least one generic buffer prior to said transferring of said incoming data for a TCP connection to at least a portion of available TCP application buffers.

20. (Original) The machine-readable storage according to claim 11, further comprising code for posting at least one posted generic buffer located in a memory internal to said host adapter.

21. (Original) A system for posting buffers for a non-posting TCP application, the system comprising:

at least one generic buffer located in a memory external to a host adapter;

at least one processor that posts said at least one generic buffer located in said memory external to said host adapter; and

said at least one processor transfers incoming data for a TCP connection to said at least one posted generic buffer prior to the non-posting TCP application posting a TCP application posted buffer for said incoming data.

22. (Original) The system according to claim 21, wherein said at least one processor allocates at least one generic buffer from a pool of available generic buffers upon receipt of said incoming data for said TCP connection.

23. (Original) The system according to claim 22, wherein said at least one processor stores at least a portion of said incoming data in said allocated at least one generic buffer if said TCP application posted buffer is unable to accommodate said incoming data.

24. (Original) The system according to claim 21, wherein said at least one processor determines whether said incoming data for said TCP connection transferred to said at least one posted generic buffer is in sequence.

25. (Original) The system according to claim 24, wherein said at least one processor assembles said incoming data in said at least one posted generic buffer if said incoming data is out of sequence.

26. (Original) The system according to claim 25, wherein said at least one processor orders said at least one posted generic buffer using a TCP data placement sequence number for said out of sequence incoming data.

27. (Original) The system according to claim 21, wherein said at least one processor polls said at least one posted generic buffer by the non-posting TCP application to determine when said at least one posted generic buffer contains data for said TCP connection.

28. (Original) The system according to claim 27, wherein said at least one processor notifies the non-posting TCP application when said incoming data is stored in said at least one posted generic buffer in response to said polling.

29. (Original) The system according to claim 21, wherein said at least one processor posts at least one generic buffer prior to said transferring of said incoming data for a TCP connection to at least a portion of available TCP application buffers.

30. (Original) The system according to claim 21, wherein said at least one processor posts at least one posted generic buffer located in a memory internal to said host adapter.

31. (Original) The system according to claim 21, wherein said at least one processor is at least one of a NIC, a generic buffer handler, a buffer post handler, an application, a TCP notifier and a TCP data placement processor.

32. (New) The method according to claim 1, further comprising copying said transferred incoming data from said posted generic buffer to said TCP application posted buffer.

33. (New) The method according to claim 32, further comprising requesting said copying of said incoming data from said posted generic buffer to said TCP application posted buffer.

34. (New) The method according to claim 32, further comprising sending at least one of a TCP sequence number, a generic consumer buffer value, a generic buffer length and a posted buffer length for said copying of said transferred incoming data.

35. (New) The machine-readable storage according to claim 11, further comprising code for copying said transferred incoming data from said posted generic buffer to said TCP application posted buffer.

36. (New) The machine-readable storage according to claim 35, further comprising code for requesting said copying of said incoming data from said posted generic buffer to said TCP application posted buffer.

37. (New) The machine-readable storage according to claim 35, further comprising code for sending at least one of a TCP sequence number, a generic consumer buffer value, a generic buffer length and a posted buffer length for said copying of said transferred incoming data.

38. (New) The system according to claim 21, wherein said at least one processor copies said transferred incoming data from said posted generic buffer to said TCP application posted buffer.

39. (New) The system according to claim 38, wherein said at least one processor requests said copying of said incoming data from said posted generic buffer to said TCP application posted buffer.

40. (New) The system according to claim 38, wherein said at least one processor sends at least one of a TCP sequence number, a generic consumer buffer value, a generic buffer length and a posted buffer length for said copying of said transferred incoming data.

41. (New) The system according to claim 21, further comprising a host adapter that copies said transferred incoming data from said posted generic buffer to said TCP application posted buffer.

42. (New) The system according to claim 41, a TCP notification process that requests said copying of said incoming data from said posted generic buffer to said TCP application posted buffer.

43. (New) The system according to claim 42, wherein said TCP notification process sends at least one of a TCP sequence number, a generic consumer buffer value, a generic buffer length and a posted buffer length for said copying of said transferred incoming data.